



#2
BT
01-18-02

Patent
Attorney's Docket No. 032986-018

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of)	
Lars SILEN et al.)	Group Art Unit: 2661
Application No.: 09/978,526)	Examiner: Unassigned
Filed: October 16, 2001)	
For: Method and Telecommunications)	
Network for Controlling an External)	
Device)	

RECEIVED
JAN 14 2002
Technology Center 2600

CLAIM FOR CONVENTION PRIORITY

Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

The benefit of the filing date of the following prior foreign application in the following foreign country is hereby requested, and the right of priority provided in 35 U.S.C. § 119 is hereby claimed:

Great Britain Patent Application No. 0025389.8

Filed: October 17, 2000

In support of this claim, enclosed is a certified copy of the prior foreign application. The prior foreign application was referred to in the oath or declaration. Acknowledgment of receipt of the certified copy is requested.

Respectfully submitted,

BURNS, DOANE, SWECKER & MATHIS, L.L.P.

Date: JANUARY 10, 2002

By: Michael J. Crowley
Michael J. Crowley
Registration No. 49,009

P.O. Box 1404
Alexandria, Virginia 22313-1404
(919) 941-9240



INVESTOR IN PEOPLE

RECEIVED
JAN 14 2002
Technology Center 2600

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation and Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein together with the Statement of inventorship and of right to grant of a Patent (Form 7/77), which was also filed.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.


Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

AmBrewster

Dated

17 October 2001



7/77

Statement of inventorship and of right to grant of a patent

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference	RL.P51278GB	
2. Patent application number <i>(if you know it)</i>	0025389.8	17 OCT 2000
3. Full name of the or of each applicant	Telefonaktiebolaget LM Ericsson	
4. Title of the invention	Method and Telecommunications Network for Controlling an External Device	
5. State how the applicant(s) derived the right from the inventor(s) to be granted a patent	By virtue of employment of the inventors	
6. How many, if any, additional Patents Forms 7/77 are attached to this form? <i>(see note (c))</i>		
7.	<p>I/We believe that the person(s) named over the page <i>(and on any extra copies of this form)</i> is/are the inventor(s) of the invention which the above patent application relates to.</p> <p>Signature <u>M. S. S. S. S.</u> Date 16 October 2000</p> <p>Marks & Clerk</p>	
8. Name and daytime telephone number of person to contact in the United Kingdom	Dr. Robert Lind	01865 397900

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500 505.
- Write your answers in capital letters using black ink or you may type them.
- If there are more than three inventors, please write the names and addresses of the other inventors on the back of another Patents Form 7/77 and attach it to this form.
- When an application does not declare any priority, or declares priority from an earlier UK application, you must provide enough copies of this form so that the Patent Office can send one to each inventor who is not an applicant.
- Once you have filled in the form you must remember to sign and date it.

Enter the full names, addresses and postcodes of the inventors in the boxes and underline the surnames

Lars Silen
Mankholmsvägen 3
2380 Esbo
Finland

Patents ADP number (if you know it): 7858814001


Jussi Saksa
Kala-Maija 2 C 28
02230 Espoo
Finland

Patents ADP number (if you know it): 8002594001

Reminder

Have you signed the form?

Patents ADP number (if you know it):



Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference

RL.P51278GB

17OCT00 E576501-6 D01063
P01/7700 0.00-0025389.8

2. Patent application number

0025389.8

(The Patent Office will fill in this part)

17 OCT 2000

3. Full name, address and postcode of the or of each applicant (*underline all surnames*)

Telefonaktiebolaget LM Ericsson
SE-12625
Stockholm
Sweden

Patents ADP number (*if you know it*)

753730003
SWEDEN

If the applicant is a corporate body, give the country/state of its incorporation

4. Title of the invention

Method and Telecommunications Network for
Controlling an External Device

5. Name of your agent (*if you have one*)

Marks & Clerk

"Address for service" in the United Kingdom to which all correspondence should be sent (*including the postcode*)

Marks & Clerk
4220 Nash Court
Oxford Business Park South
Oxford
OX4 2RU

Patents ADP number (*if you know it*)

727 1125 001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (*if you know it*) the or each application number

Country

Priority application number
(*if you know it*)

Date of filing
(*day / month / year*)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(*day / month / year*)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (*Answer 'Yes' if:*

Yes

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form (none)

Description 10

Claim(s) 3

Abstract 1

Drawing(s) 2

10. If you are also filing any of the following, state how many against each item.

Priority documents (none)

Translations of priority documents (none)

Statement of inventorship and right to grant of a patent (Patents Form 7/77) 1 /

Request for preliminary examination and search (Patents Form 9/77) 1 /

Request for substantive examination (Patents Form 10/77) 1 ✓

Any other documents (none)
(please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature

Marks & Clerk

Date

16 October, 2000

12. Name and daytime telephone number of person to contact in the United Kingdom

Dr. Robert Lind 01865 397900

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.




Figure 1





Figure 3

Figure 2

METHOD AND TELECOMMUNICATIONS NETWORK FOR CONTROLLING AN EXTERNAL DEVICE

The present invention relates to a method of controlling an external device. The present invention also relates to a telecommunications network for performing such a method.

WO 09956447A discloses a technique for permitting automatic configuring of network appliances such as internet-compatible telephones. An HTML page is accessed using a browser application and data from the page is downloaded. The HTML code is parsed so as to identify configuration information, which is transmitted to a telephone. The telephone is thus configured in accordance with this information by a user who does not need to make use of any programming languages.

US 5 875 242 discloses a system for controlling and updating telecommunications devices such as exchanges. A local database within the system provides real-time or near real-time access and modification of programming information for the telecommunications equipment. Individual items of equipment can have their program information updated from the system which may thus provide a single or central control point for various items of telecommunications equipment.

US 6 047 071 discloses a technique which allows updating of system parameters of a mobile phone. In particular, when the mobile telephone parameters are to be updated, a secure communication link to a telecommunications network is established to allow updated parameter values to be transmitted to the mobile phone and stored therein for future use.

Mobile phones are known which allow text messages to be transmitted and received. For example, in the case of GSM mobile telephones, text messages may be sent by a communication link which is distinct from the link provided for voice or speech communication. Such messages are known as SMS messages and are defined within the GSM standard.

According to a first aspect of the invention, there is provided a method of controlling an external device, comprising the steps of:
sending a control request from a terminal to a telecommunications network;
converting the request into a control code; and
sending the control code from the telecommunications network to the external device.

The terminal may be a mobile wireless terminal such as a cellular telephone or communicator. The control request may be sent from the terminal to the telecommunications network using a text messaging service.

Preferably, the control code is sent from the telecommunications network to the external device using a text messaging service. Text messaging may be used over a whole or a part of the transmission path. Alternatively, the control code may be sent to the external device using e-mail or a web or WAP download.

The external device may be associated with or may form part of the terminal. For example, the terminal may be coupled to the external device via a local wireless link, e.g. Bluetooth or infra-red. Alternatively, the external device may be remote from the terminal. The external device may have a telecommunications receiver, e.g. a wireless data card.

The step of sending a control request may comprise dialling a service telephone number of the telecommunications network.

The control request may include an identifier identifying the terminal. The destination of the control code may be determined by the identifier.

The telecommunications network may interact with the terminal to select one of a plurality of predetermined control codes for sending to the external device. The interaction may be at least partly via a speech channel or may use the Wireless Application Protocol.

In response to receipt of the control code, the external device may send, or cause to be sent, a response comprising at least part of a text message to the telecommunications network. The telecommunications network may send at least part of the response as at least part of a further text message to the terminal.

According to a second aspect of the invention, there is provided a telecommunications network for performing a method according to the first aspect of the invention.

According to a third aspect of the invention, there is provided a telecommunications network comprising means for converting a control request from a terminal to a control code and means for sending the control code to an external device for controlling the external device.

The network may comprise a computer.

According to a fourth aspect of the invention, there is provided a program for controlling a computer of a network according to the second or third aspect of the invention.

According to a fifth aspect of the invention, there is provided a medium containing a program according to the fourth aspect of the invention.

It is thus possible to provide a reliable and convenient way of controlling an external device via a telecommunications network from a terminal, such as a mobile telephone (or communicator or PDA having a wireless telephone capability) or other type of telephone. In the case of a mobile telephone, for example, it is unnecessary to store any control codes in the telephone, which may comprise sequences of commands and which would otherwise occupy substantial amounts of memory. Although it would be possible to convert control requests to control codes within such a mobile telephone, this would require significant amounts of processing power and memory within the mobile telephone. Instead, relatively simply control requests may be sent to the telecommunications network. For example, it may be necessary merely to send a service number to the telecommunications network. Where a choice of controlled

actions is possible, this may be performed interactively, for example by receiving voice prompts from the telecommunications network and making selections using the dialling keypad of the mobile telephone.

In the case of telephones which are not equipped for sending text messages, such as many conventional telephones connected by cables to telephone exchanges, control of external devices may nevertheless be provided. It is merely necessary for the conventional telephone to form the control request, which may be no more than a service telephone number to be recognised by the telecommunications network.

Control of external devices may require that the control codes be completely accurate. For example, the external devices may require complex codes or sequences of commands in a predetermined order. These may be predefined and stored within the telecommunications network. Thus, whenever a control request is received, it is ensured that accurate control codes are reliably produced and sent to the external devices so as to ensure substantially completely reliable control of the devices. In general, the control requests are much simpler than the resulting control codes so that the number of errors can be greatly reduced or substantially eliminated. In order to provide a variety or large number of control functions, a corresponding number of control codes are necessary. However, by predefining these and effectively selecting them by much simpler control requests, the processing and memory requirements are located within the telecommunications network so that substantially no processing or memory resources have to be provided within the terminals. Where the terminals are telephones, this reduces the complexity and cost, particularly of mobile telephones where compactness and extended battery life are important requirements.

The invention will be further described, by way of example, with reference to the accompanying drawings, in which:

Figure 1 is a schematic diagram of a first telecommunications system constituting a first embodiment of the invention;

Figure 2 is a flow diagram illustrating a method of obtaining a control code for controlling an external device; and

Figure 3 is a schematic diagram of a second telecommunications system constituting a second embodiment of the invention.

Figure 1 shows a telecommunications network 1 which includes a cellular radio telephone network. A portable cellular telephone 2, illustrated as being of GSM type (the telephone may conform to any other appropriate standard such as UMTS), is associated with an external device 3 which is to be controlled by means of messages from the telephone 2. The telephone 2 and the external device are located adjacent each other and are coupled together, for example by a Bluetooth wireless link 4 (alternatively the telephone 2 and the device 3 may together form a single integrated device).

The telephone 2 has a keypad 5 for dialling and other purposes. In particular, the keypad 5 allows text messages to be composed and transmitted as SMS messages via the cellular radio network (forming part of the network 1) to other terminals which have the capability of receiving and displaying such messages. SMS messages may also be sent to, and terminate at, nodes of the network 1.

In order to control some function or operation of the external device 3, a user enters a control request by means of the keypad 5 of the telephone 2. The telephone 2 transmits the control request to the network 1 in an SMS message. The network includes a command sequence programming interface 6 and a compiler 7 for handling the received SMS message. The interface 6 represents the destination for the SMS message.

The interface 6 recognises the content of the received SMS message as a control request for controlling the external device 3, and passes the request to the compiler 7. The compiler 7 converts the control request into a control code which is suitable, for example without any further processing, for being supplied to the external device 3 in order to perform the desired control operation of the device. For example, the control request may be supplied by the compiler 7 to a previously created database which, as a result, supplies a control code, which may be a single code word or command or may comprise an ordered sequence of code words or commands, to the compiler 7.

In a typical arrangement where a control code is required to produce a predetermined control operation or function of the device 3, the corresponding database entry is required to identify the device and this may be achieved by identifying the A number of the telephone 2 which sent the control request. The entry in the database may, therefore, be in the form of a look-up table associated with a short software routine for producing the desired control code. During the programming phase of the database, the compiler 7 compiles the appropriate control code and checks this for errors. The resulting database entry is then available for subsequent control requests. It is therefore ensured that, whenever the control request is received, the correct control code is reliably produced and sent to the external device.

The control code is embedded in an SMS message and is transmitted by the network 1 to the telephone 2 (typically via an SMS server which is not shown in Figure 1). Upon receipt of this SMS message, the telephone 2 extracts the control code and supplies this to the external device 3 via the Bluetooth link 4. The receipt of the control code by the device 3 results in the desired function or operation being performed by the device. This process is further illustrated in the flow diagram of Figure 2.

Figure 1 also illustrates an arrangement for creating and modifying entries in the network database which maps control requests to corresponding control codes. A personal computer (PC) 8 is connected to the network 1 and, particularly, to the compiler 7 via the Internet 9. The compiler 7 compiles control codes received from the PC 8 and performs error checking to ensure that there are no errors in the compiled control codes. The codes may be supplied by the PC 6 as an e-mail or as an attachment to an e-mail. As an alternative, the codes may be entered using a worldwide web (WWW) page (the compiler 7 is for example a WWW-based command sequence programming interface, for example based on Java or CGI programming languages or texts). Where mobile Internet is available, WAP may be used. This arrangement affords great flexibility to users as they are not restricted to control codes made available by the network operator.

Although Figure 1 illustrates the external device 3 as being associated with the telephone 2, the external device may be located elsewhere and may be associated with a

second mobile telephone. This second telephone may receive control codes sent from the first telephone 2 using SMS messages, or sent from the network in response to a request from the first telephone 2, and relay these to the external device 3. The device 3 does not need to be provided with a telephone *per se* but instead may make use of a GSM module in order to be able to receive and extract the control codes embedded within SMS messages, in which case the database within the compiler 7 is required to store the B number of the module so as to establish a connection to the module in order to transmit the SMS messages.

In another arrangement, the external device 3 may be associated with other equipment connected to or forming part of the network 1, being remote from the "controlling" telephone 2. Such an arrangement is illustrated in Figure 3. For example, the external device 3 may be associated with a PC 10 and the control codes may be supplied via e-mail as illustrated at 11 or as a (manually) downloadable web page as illustrated at 12, following a request from the controlling mobile phone 3. If the external device has an SMS interface, the PC 10 may convert the received e-mail into an SMS format for transmission to the external device 3.

The present invention may be employed where the controlling telephone is of a type which is not capable of sending text messages. Figure 3 illustrates such a telephone 13. A user dials a service telephone number corresponding to the desired control function of the device 3 - the connection being made via a PSTN network 14. The network is notified of the call and accesses the database to identify the appropriate control code. The control code is embedded in an e-mail message for sending to the PC 10. It will be appreciated that, where the external device 3 has a GSM module, the control code may be sent to the external device in an SMS message.

In order to select between several control functions or operations of the external device 3, the database used by the compiler 7 may be programmed to provide several options in response to a control request and may interact with the controlling terminal to allow a user to select which function or operation is to be performed. For example, when the A number of the terminal is recognised by the server 11 following the receipt of a control request, a voice-prompting system may be actuated. Pre-recorded or synthesised voice

messages are played to the telephone 2,13, for example asking the user to select from a menu of options by pressing the appropriate key or combination of keys on the keypad of the terminal. The resulting DTMF codes are received by the compiler 7 to select the appropriate menu item. This may be repeated one or more times for nested menus. Once the desired operation or function has been selected, the appropriate control code in the form of the pre-programmed command sequence is embedded in an SMS message or e-mail (or made available via a www page) and transmitted to the external device (via the telephone 2,13 or PC 10). The correct control code for the desired operation or function is thus supplied to the external device 3, which in turn provides a desired response.

It is thus possible to provide a control arrangement which does not require the storage of control sequences, and hence the provision of sufficient memory capacity, within the telephones 2, 13. Further, it is unnecessary for a user to enter lengthy command sequences manually. Syntactically correct codes are generated so that the complexity and cost of providing syntax checks within the external devices 3 can be greatly simplified or eliminated. Thus, simpler and cheaper microcontrollers may be used in the external devices 3. A user without a GSM telephone or with a GSM telephone without support for SMS messages may still control an external device, for example simply by dialling the appropriate service number as described hereinabove. The external devices to be controlled merely require sufficient intelligence to extract the resulting control codes generated within the telecommunications network from the SMS messages, e-mail, or WWW/WAP page.

This arrangement may be used for many applications, for example where remote control of an external device is required. The following are merely specific examples of the enormous range of possible applications.

Electricity supply meters, for example for homes or offices, may be connected to respective mobile telephone modules having a suitable interface. The electricity supplier may read a meter by telephoning the appropriate predetermined service number. When the telecommunications network receives the telephone call, a control code is sent to a first of the mobile telephone modules and the associated electricity

meter to cause the meter reading to be converted into an SMS message and to be transmitted back to the original calling terminal or telephone at the electricity supplier. The electricity supplier may then repeat this operation and the database may step to a next user each time the control request is received. Thus, a large number of electricity meters may be read one at a time in sequence and automatically. Such an arrangement ensures that the electricity supplier cannot cause a serious load on the network by attempting to read large numbers, such as thousands, of meters at substantially the same time.

A house or office heating system may include a room thermostat whose temperature can be set electronically. Thus, a user may dial the appropriate service number in order to commence control of the temperature setting of the thermostat and may then use the telephone keypad to supply DTMF codes in order to set the thermostat temperature to a desired value.

It is possible to provide a control sequence in order to open an electronic lock by using this type of arrangement. For example, the database may be arranged to generate the appropriate control sequence upon receipt of a request from a telephone whose A-number is identified as being authorised to open the lock.

It will be appreciated by the person of skill in the art that various modifications may be made to the above described embodiments without departing from the scope of the present invention. Modifications include:

- sending a control code request from a PC, mobile phone/communicator, or PDA via e-mail or the Internet to the network, where the control code is identified and sent to the control device;
- requesting a control code from the network using a mobile wireless device, and returning the control code to that device, from where it can be sent to a second mobile device coupled to the external device to be controlled;
- providing the compiler 7 outside the telecommunications network, such that a request for a control code is forwarded from the network to the external compiler. The compiler then returns the control code to the network (or possibly sends it directly to the external device);

- where a control code is sent from a device as an SMS message, but the external device is capable of receiving only e-mail, an SMS to e-mail conversion may be performed at some point in the transmission path.

CLAIMS:

1. A method of controlling an external device, comprising the steps of:
sending a control request from a terminal to a telecommunications network;
converting the request into a control code; and
sending the control code from the telecommunications network to the external device.
2. A method according to claim 1, wherein the terminal is a mobile wireless terminal.
3. A method according to claim 2, wherein the control request is sent from the terminal to the telecommunications network using a text messaging service.
4. A method according to any one of the preceding claims, wherein the control code is sent from the telecommunications network to the external device using a text messaging service.
5. A method according to any one of the preceding claims, wherein the external device is associated with or forms part of the terminal.
6. A method according to claim 5, wherein the terminal is coupled to the external device via a local wireless link.
7. A method according to claim 5 or 6, wherein the control code is delivered to the external device via said terminal.
8. A method according to any one of claims 1 to 4, wherein the external device is remote from the terminal.
9. A method according to claim 8, wherein the external device comprises a telecommunications receiver.

10. A method according to claim 9 when appended to claim 3, wherein said telecommunications receiver receives a text message containing said control code.
11. A method according to claim 1, in which the step of sending a control request to the telecommunications network comprises calling a service telephone number.
12. A method as claimed in any one of the preceding claims, in which the telecommunications network interacts with the terminal to select one of a plurality of predetermined control codes for sending to the external device.
13. A method as claimed in claim 12, in which the interaction is at least partly via a speech channel.
14. A method as claimed in any one of the preceding claims, in which, in response to receipt of the control code, the external device sends a response comprising at least part of a text message to the telecommunications network.
15. A method as claimed in claim 14, in which the telecommunications network sends at least part of the response as at least part of a further text message to the terminal.
16. A telecommunications network for performing a method as claimed in any one of the preceding claims.
17. A telecommunications network comprising means for converting a control request from a terminal to a control code and means for sending the control code to an external device for controlling the external device.
18. A network as claimed in claim 17, in which the control request includes an identifier identifying the terminal.
19. A network as claimed in claim 18, in which the sending means is arranged to send the control code to a destination determined by the identifier.

20. A network as claimed in any one of claims 17 to 19, in which the control code is predetermined and the sending means is arranged to send the control code in response to receipt of the service number.
21. A network as claimed in any one of claims 17 to 19, comprising means for interacting with the terminal to select one of a plurality of predetermined control codes for sending to the external device.
22. A network as claimed in claim 21, in which the interacting means is arranged to interact with the terminal at least partly via a speech channel.
23. A network as claimed in any one of claims 16 to 22, comprising a computer.
24. A program for controlling a computer of a network as claimed in claim 23 to perform a method as claimed in any one of claims 1 to 15.
25. A medium containing a program as claimed in claim 24.

ABSTRACT
METHOD AND TELECOMMUNICATIONS NETWORK FOR
CONTROLLING AN EXTERNAL DEVICE

In order to control an external device 3, which may be associated with or remote from a terminal such as a mobile telephone 2, the terminal 2 sends a control request, for example in the form of an SMS message, to a telecommunications network 1. The network 1 converts the request into a control code which is in a form ready for controlling the external device 3. The control code is embedded in an SMS message which is then transmitted from the network 1 to the device 3, which has a GSM or other module associated with it in order to allow the embedded control code to be received, extracted, and supplied to the device 3 to perform the requested operation or function.

(Fig. 1)